

Sorting in linear time

Counting sort:
 All elements are integers
 No comparisons between elements.

- **Input:** $A[1 \dots n]$, where $A[j] \in \{1, 2, \dots, k\}$.
- **Output:** $B[1 \dots n]$, sorted
- **Auxiliary storage:** $C[1 \dots k]$.

© Alon Efrat Introduction to Algorithms L5.1

Counting sort

```

for i ← 1 to k
  do C[i] ← 0
for j ← 1 to n
  do C[A[j]] ++
  /* After this step, C[i] contains num of elements
  whose key = i */
for i ← 2 to k
  do C[i] ← C[i] + C[i-1]
  /* After this step C[i] = |{key ≤ i}| */
  /* C indicates where to put the next A[j] when copying B ← A */
for j ← n downto 1
  do x ← A[j]
     B[C[x]] ← x
     C[x] --
    
```

© Alon Efrat Introduction to Algorithms L5.2

Counting-sort example

A:

1	2	3	4	5
4	1	3	4	3

 C:

1	2	3	4

B:

--	--	--	--	--

© Alon Efrat Introduction to Algorithms L5.3

Loop 1

A:

1	2	3	4	5
4	1	3	4	3

 C:

1	2	3	4
0	0	0	0

B:

--	--	--	--	--

```

for i ← 1 to k
  do C[i] ← 0
    
```

© Alon Efrat Introduction to Algorithms L5.4

Loop 2

A:

1	2	3	4	5
4	1	3	4	3

 C:

1	2	3	4
0	0	0	1

B:

--	--	--	--	--

for $j \leftarrow 1$ **to** n
do $C[A[j]] \leftarrow C[A[j]] + 1 \triangleright C[i] = |\{\text{key} = i\}|$

© Alon Efrat Introduction to Algorithms L5.5

Loop 2

A:

1	2	3	4	5
4	1	3	4	3

 C:

1	2	3	4
1	0	0	1

B:

--	--	--	--	--

for $j \leftarrow 1$ **to** n
do $C[A[j]] \leftarrow C[A[j]] + 1 \triangleright C[i] = |\{\text{key} = i\}|$

© Alon Efrat Introduction to Algorithms L5.6

Loop 2

A:

1	2	3	4	5
4	1	3	4	3

 C:

1	2	3	4
1	0	1	1

B:

--	--	--	--	--

for $j \leftarrow 1$ **to** n
do $C[A[j]] \leftarrow C[A[j]] + 1 \triangleright C[i] = |\{\text{key} = i\}|$

© Alon Efrat Introduction to Algorithms L5.7

Loop 2

A:

1	2	3	4	5
4	1	3	4	3

 C:

1	2	3	4
1	0	1	2

B:

--	--	--	--	--

for $j \leftarrow 1$ **to** n
do $C[A[j]] \leftarrow C[A[j]] + 1 \triangleright C[i] = |\{\text{key} = i\}|$

© Alon Efrat Introduction to Algorithms L5.8

Loop 2

A:

1	2	3	4	5
4	1	3	4	3

 C:

1	2	3	4
1	0	2	2

B:

--	--	--	--	--

for $j \leftarrow 1$ **to** n
do $C[A[j]] \leftarrow C[A[j]] + 1 \quad \triangleright C[i] = |\{\text{key} = i\}|$

© Alon Efrat Introduction to Algorithms L5.9

Loop 3

A:

1	2	3	4	5
4	1	3	4	3

 C:

1	2	3	4
1	0	2	2

B:

--	--	--	--	--

 C':

1	1	2	2
---	---	---	---

for $i \leftarrow 2$ **to** k
do $C[i] \leftarrow C[i] + C[i-1] \quad \triangleright C[i] = |\{\text{key} \leq i\}|$

© Alon Efrat Introduction to Algorithms L5.10

Loop 3

A:

1	2	3	4	5
4	1	3	4	3

 C:

1	2	3	4
1	0	2	2

B:

--	--	--	--	--

 C':

1	1	3	2
---	---	---	---

for $i \leftarrow 2$ **to** k
do $C[i] \leftarrow C[i] + C[i-1] \quad \triangleright C[i] = |\{\text{key} \leq i\}|$

© Alon Efrat Introduction to Algorithms L5.11

Loop 3

A:

1	2	3	4	5
4	1	3	4	3

 C:

1	2	3	4
1	0	2	2

B:

--	--	--	--	--

 C':

1	1	3	5
---	---	---	---

for $i \leftarrow 2$ **to** k
do $C[i] \leftarrow C[i] + C[i-1] \quad \triangleright C[i] = |\{\text{key} \leq i\}|$

© Alon Efrat Introduction to Algorithms L5.12

Loop 4

<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">2</td><td style="padding: 0 5px;">3</td><td style="padding: 0 5px;">4</td><td style="padding: 0 5px;">5</td></tr> <tr><td style="border: 1px solid gray; padding: 2px;">4</td><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; padding: 2px;">4</td><td style="border: 1px solid gray; padding: 2px;">3</td></tr> </table>	1	2	3	4	5	4	1	3	4	3	<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">2</td><td style="padding: 0 5px;">3</td><td style="padding: 0 5px;">4</td></tr> <tr><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; padding: 2px;">5</td></tr> </table>	1	2	3	4	1	1	3	5
1	2	3	4	5															
4	1	3	4	3															
1	2	3	4																
1	1	3	5																
<table style="margin: auto;"> <tr><td style="border: 1px solid gray; width: 20px; height: 20px;"></td><td style="border: 1px solid gray; width: 20px; height: 20px;"></td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; width: 20px; height: 20px;"></td><td style="border: 1px solid gray; width: 20px; height: 20px;"></td></tr> </table>			3			<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">2</td><td style="padding: 0 5px;">5</td></tr> </table>	1	1	2	5									
		3																	
1	1	2	5																

for $j \leftarrow n$ **downto** 1
do $x \leftarrow A[j]$
 $B[C[x]] \leftarrow x$
 $C[x] \leftarrow C[x]$ —

© Alon Efrat Introduction to Algorithms L5.13

Loop 4

<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">2</td><td style="padding: 0 5px;">3</td><td style="padding: 0 5px;">4</td><td style="padding: 0 5px;">5</td></tr> <tr><td style="border: 1px solid gray; padding: 2px;">4</td><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; padding: 2px;">4</td><td style="border: 1px solid gray; padding: 2px;">3</td></tr> </table>	1	2	3	4	5	4	1	3	4	3	<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">2</td><td style="padding: 0 5px;">3</td><td style="padding: 0 5px;">4</td></tr> <tr><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">2</td><td style="border: 1px solid gray; padding: 2px;">5</td></tr> </table>	1	2	3	4	1	1	2	5
1	2	3	4	5															
4	1	3	4	3															
1	2	3	4																
1	1	2	5																
<table style="margin: auto;"> <tr><td style="border: 1px solid gray; width: 20px; height: 20px;"></td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; width: 20px; height: 20px;"></td><td style="border: 1px solid gray; padding: 2px;">4</td><td style="border: 1px solid gray; width: 20px; height: 20px;"></td></tr> </table>		3		4		<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">2</td><td style="padding: 0 5px;">4</td></tr> </table>	1	1	2	4									
	3		4																
1	1	2	4																

for $j \leftarrow n$ **downto** 1
do $x \leftarrow A[j]$
 $B[C[x]] \leftarrow x$
 $C[x] \leftarrow C[x]$ —

© Alon Efrat Introduction to Algorithms L5.14

Loop 4

<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">2</td><td style="padding: 0 5px;">3</td><td style="padding: 0 5px;">4</td><td style="padding: 0 5px;">5</td></tr> <tr><td style="border: 1px solid gray; padding: 2px;">4</td><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; padding: 2px;">4</td><td style="border: 1px solid gray; padding: 2px;">3</td></tr> </table>	1	2	3	4	5	4	1	3	4	3	<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">2</td><td style="padding: 0 5px;">3</td><td style="padding: 0 5px;">4</td></tr> <tr><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">2</td><td style="border: 1px solid gray; padding: 2px;">4</td></tr> </table>	1	2	3	4	1	1	2	4
1	2	3	4	5															
4	1	3	4	3															
1	2	3	4																
1	1	2	4																
<table style="margin: auto;"> <tr><td style="border: 1px solid gray; width: 20px; height: 20px;"></td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; width: 20px; height: 20px;"></td><td style="border: 1px solid gray; padding: 2px;">4</td></tr> </table>		3	3		4	<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">4</td></tr> </table>	1	1	1	4									
	3	3		4															
1	1	1	4																

for $j \leftarrow n$ **downto** 1
do $x \leftarrow A[j]$
 $B[C[x]] \leftarrow x$
 $C[x] \leftarrow C[x]$ —

© Alon Efrat Introduction to Algorithms L5.15

Loop 4

<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">2</td><td style="padding: 0 5px;">3</td><td style="padding: 0 5px;">4</td><td style="padding: 0 5px;">5</td></tr> <tr><td style="border: 1px solid gray; padding: 2px;">4</td><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; padding: 2px;">4</td><td style="border: 1px solid gray; padding: 2px;">3</td></tr> </table>	1	2	3	4	5	4	1	3	4	3	<table style="margin: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">2</td><td style="padding: 0 5px;">3</td><td style="padding: 0 5px;">4</td></tr> <tr><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">4</td></tr> </table>	1	2	3	4	1	1	1	4
1	2	3	4	5															
4	1	3	4	3															
1	2	3	4																
1	1	1	4																
<table style="margin: auto;"> <tr><td style="border: 1px solid gray; padding: 2px;">1</td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; padding: 2px;">3</td><td style="border: 1px solid gray; width: 20px; height: 20px;"></td><td style="border: 1px solid gray; padding: 2px;">4</td></tr> </table>	1	3	3		4	<table style="margin: auto;"> <tr><td style="padding: 0 5px;">0</td><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">4</td></tr> </table>	0	1	1	4									
1	3	3		4															
0	1	1	4																

for $j \leftarrow n$ **downto** 1
do $x \leftarrow A[j]$
 $B[C[x]] \leftarrow x$
 $C[x] \leftarrow C[x]$ —

© Alon Efrat Introduction to Algorithms L5.16

Loop 4

A:

1	2	3	4	5
4	1	3	4	3

B:

1	3	3	4	4
---	---	---	---	---

C:

1	2	3	4
0	1	1	4

C':

0	1	1	3
---	---	---	---

for $j \leftarrow n$ **downto** 1
do $x \leftarrow A[j]$
 $B[C[x]] \leftarrow x$
 $C[x] \leftarrow C[x] - 1$

© Alon Efrat
Introduction to Algorithms
L5.17

Analysis

$\Theta(k)$ { **for** $i \leftarrow 1$ **to** k
 do $C[i] \leftarrow 0$
 $\Theta(n)$ { **for** $j \leftarrow 1$ **to** n
 do $C[A[j]] \leftarrow C[A[j]] + 1$
 $\Theta(k)$ { **for** $i \leftarrow 2$ **to** k
 do $C[i] \leftarrow C[i] + C[i-1]$
 $\Theta(n)$ { **for** $j \leftarrow n$ **downto** 1
 do $x \leftarrow A[j]$
 $B[C[x]] \leftarrow x$
 $C[x] \leftarrow C[x] - 1$

 $\Theta(n + k)$

© Alon Efrat
Introduction to Algorithms
L5.18

Stable sorting

Counting sort is a *stable* sort: it preserves the input order among equal elements.

A:

4	1	3	4	3
---	---	---	---	---

B:

1	3	3	4	4
---	---	---	---	---

Exercise: What other sorts have this property?

© Alon Efrat
Introduction to Algorithms
L5.19

Radix sort

- Used (for example) to sort integers in the range 0 to 10000.
- In general – good for any **lexicographic** sorting.
- **Origin:** Herman Hollerith's card-sorting machine for the 1890 U.S. Census. (See Appendix .)
- Digit-by-digit sort.
- Hollerith's original (bad) idea: sort on most-significant digit first.
- Good idea: Sort on **least-significant digit first** with auxiliary *stable* sort.

© Alon Efrat
Introduction to Algorithms
L5.20

Operation of radix sort

3 2 9	7 2 0	7 2 0	3 2 9
4 5 7	3 5 5	3 2 9	3 5 5
6 5 7	4 3 6	4 3 6	4 3 6
8 3 9	4 5 7	8 3 9	4 5 7
4 3 6	6 5 7	3 5 5	6 5 7
7 2 0	3 2 9	4 5 7	7 2 0
3 5 5	8 3 9	6 5 7	8 3 9

© Alon Efrat Introduction to Algorithms L5.21

Correctness of radix sort

Induction on digit position

- Assume that the numbers are sorted by their low-order $t - 1$ digits.
- Sort on digit t

7 2 0	3 2 9
3 2 9	3 5 5
4 3 6	4 3 6
8 3 9	4 5 7
3 5 5	6 5 7
4 5 7	7 2 0
6 5 7	8 3 9

© Alon Efrat Introduction to Algorithms L5.22

Correctness of radix sort

Induction on digit position

- Assume that the numbers are sorted by their low-order $t - 1$ digits.
- Sort on digit t
 - Two numbers that differ in digit t are correctly sorted.

7 2 0	3 2 9
3 2 9	3 5 5
4 3 6	4 3 6
8 3 9	4 5 7
3 5 5	6 5 7
4 5 7	7 2 0
6 5 7	8 3 9

© Alon Efrat Introduction to Algorithms L5.23

Correctness of radix sort

Induction on digit position

- Assume that the numbers are sorted by their low-order $t - 1$ digits.
- Sort on digit t
 - Two numbers that differ in digit t are correctly sorted.
 - Two numbers equal in digit t are put in the same order as the input \Rightarrow correct order.

7 2 0	3 2 9
3 2 9	3 5 5
4 3 6	4 3 6
8 3 9	4 5 7
3 5 5	6 5 7
4 5 7	7 2 0
6 5 7	8 3 9

© Alon Efrat Introduction to Algorithms L5.24

Analysis of radix sort

- Assume counting sort is the auxiliary stable sort.
- Sort n computer words of b bits each.
- Each word can be viewed as having b/r base- 2^r digits.

Example: 32-bit word 

$r = 8 \Rightarrow b/r = 4$ passes of counting sort on base- 2^8 digits; or $r = 16 \Rightarrow b/r = 2$ passes of counting sort on base- 2^{16} digits.

How many passes should we make?

© Alon Efrat

Introduction to Algorithms

L5.25

Analysis (continued)

Recall: Counting sort takes $\Theta(n + k)$ time to sort n numbers in the range from 0 to $k - 1$.

If each b -bit word is broken into r -bit pieces, each pass of counting sort takes $\Theta(n + 2^r)$ time. Since there are b/r passes, we have

$$T(n, b) = \Theta\left(\frac{b}{r}(n + 2^r)\right).$$

Choose r to minimize $T(n, b)$:

- Increasing r means fewer passes, but as $r \gg \lg n$, the time grows exponentially.

© Alon Efrat

Introduction to Algorithms

L5.26

Choosing r

$$T(n, b) = \Theta\left(\frac{b}{r}(n + 2^r)\right)$$

Minimize $T(n, b)$ by differentiating and setting to 0.

Or, just observe that we don't want $2^r \gg n$, and there's no harm asymptotically in choosing r as large as possible subject to this constraint.

Choosing $r = \lg n$ implies $T(n, b) = \Theta(bn/\lg n)$.

- For numbers in the range from 0 to $n^d - 1$, we have $b = d \lg n \Rightarrow$ radix sort runs in $\Theta(dn)$ time.

© Alon Efrat

Introduction to Algorithms

L5.27

Conclusions

In practice, radix sort is fast for large inputs, as well as simple to code and maintain.

Example (32-bit numbers):

- At most 3 passes when sorting ≥ 2000 numbers.
- Merge sort and quicksort do at least $\lceil \lg 2000 \rceil = 11$ passes.

Downside: Unlike quicksort, radix sort displays little locality of reference, and thus a well-tuned quicksort fares better on modern processors, which feature steep memory hierarchies.

© Alon Efrat

Introduction to Algorithms


L5.28

Appendix: Punched-card technology

- Herman Hollerith (1860-1929)
- Punched cards
- Hollerith's tabulating system
- Operation of the sorter
- Origin of radix sort
- "Modern" IBM card
- Web resources on punched-card technology

© Alon Efrat Introduction to Algorithms L5.29

Herman Hollerith (1860-1929)




- The 1880 U.S. Census took almost 10 years to process.
- While a lecturer at MIT, Hollerith prototyped punched-card technology.
- His machines, including a "card sorter," allowed the 1890 census total to be reported in 6 weeks.
- He founded the Tabulating Machine Company in 1911, which merged with other companies in 1924 to form International Business Machines.

© Alon Efrat Introduction to Algorithms L5.30

Punched cards

- Punched card = data record.
- Hole = value.
- Algorithm = machine + human operator.



Replica of punch card from the 1900 U.S. census. [Howells 2000]

© Alon Efrat Introduction to Algorithms L5.31

Lower bound for Comparison-based sort

Most of the sorting algorithms we have seen so far (excluding counting and Radix) are *comparison sorts*: only use comparisons to determine the relative order of elements.

- E.g., insertion sort, merge sort, quicksort, heapsort.

The best worst-case running time that we've seen for comparison sorting is $O(n \lg n)$.

Is $O(n \lg n)$ the best we can do?

Decision trees can help us answer this question.

© Alon Efrat Introduction to Algorithms L5.32

Decision-tree example

Sort $\langle a_1, a_2, \dots, a_n \rangle$

Each internal node is labeled $i:j$ for $i, j \in \{1, 2, \dots, n\}$.

- The left subtree shows subsequent comparisons if $a_i \leq a_j$.
- The right subtree shows subsequent comparisons if $a_i \geq a_j$.

© Alon Efrat Introduction to Algorithms L5.33

Decision-tree example

Sort $\langle a_1, a_2, a_3 \rangle$
 $= \langle 9, 4, 6 \rangle$:

Each internal node is labeled $i:j$ for $i, j \in \{1, 2, \dots, n\}$.

- The left subtree shows subsequent comparisons if $a_i \leq a_j$.
- The right subtree shows subsequent comparisons if $a_i \geq a_j$.

© Alon Efrat Introduction to Algorithms L5.34

Decision-tree example

Sort $\langle a_1, a_2, a_3 \rangle$
 $= \langle 9, 4, 6 \rangle$:

Each internal node is labeled $i:j$ for $i, j \in \{1, 2, \dots, n\}$.

- The left subtree shows subsequent comparisons if $a_i \leq a_j$.
- The right subtree shows subsequent comparisons if $a_i \geq a_j$.

© Alon Efrat Introduction to Algorithms L5.35

Decision-tree example

Sort $\langle a_1, a_2, a_3 \rangle$
 $= \langle 9, 4, 6 \rangle$:

Each internal node is labeled $i:j$ for $i, j \in \{1, 2, \dots, n\}$.

- The left subtree shows subsequent comparisons if $a_i \leq a_j$.
- The right subtree shows subsequent comparisons if $a_i \geq a_j$.

© Alon Efrat Introduction to Algorithms L5.36

Decision-tree example

Sort $\langle a_1, a_2, a_3 \rangle$
 $= \langle 9, 4, 6 \rangle$:

$4 \leq 6 \leq 9$

Each leaf contains a permutation $\langle \pi(1), \pi(2), \dots, \pi(n) \rangle$ to indicate that the ordering $a_{\pi(1)} \leq a_{\pi(2)} \leq \dots \leq a_{\pi(n)}$ has been established. (e.g. $\langle \pi(1)=a_2, \pi(2)=a_3, \pi(3)=a_1 \rangle$)

© Alon Efrat Introduction to Algorithms L5.37

Decision-tree model

A decision tree can model the execution of any comparison sort:

- One tree for each input size n .
- View the algorithm as splitting whenever it compares two elements.
- The tree contains the comparisons along all possible instruction traces.
- The running time of the algorithm = the length of the path taken.
- Worst-case running time = height of tree.

© Alon Efrat Introduction to Algorithms L5.38

Lower bound for decision-tree sorting

Theorem. Any decision tree that can sort n elements must have height $\Omega(n \lg n)$.

Proof. The tree must contain $\geq n!$ leaves, since there are $n!$ possible permutations. A height- h binary tree has $\leq 2^h$ leaves. Thus, $n! \leq 2^h$.

$\therefore h \geq \lg(n!) \quad (\lg \text{ is mono. increasing})$
 $\geq \lg((n/e)^n) \quad (\text{Stirling's formula})$
 $= n \lg n - n \lg e$
 $= \Omega(n \lg n). \quad \square$

© Alon Efrat Introduction to Algorithms L5.39

Lower bound for comparison sorting

Corollary. Merge sort is an asymptotically optimal comparison sorting algorithm. □

© Alon Efrat Introduction to Algorithms L5.40

Hollerith's tabulating system

- Pantograph card punch
- Hand-press reader
- Dial counters
- Sorting box

THE FIRST "HOLLERITH" GENERAL CENTER COUNTING MACHINE 1890

Figure from [Howells 2000].

© Alon Efrat Introduction to Algorithms L5.41

Appendix: Operation of Hollerith sorter

- An operator inserts a card into the press.
- Pins on the press reach through the punched holes to make electrical contact with mercury-filled cups beneath the card.
- Whenever a particular digit value is punched, the lid of the corresponding sorting bin lifts.
- The operator deposits the card into the bin and closes the lid.
- When all cards have been processed, the front panel is opened, and the cards are collected in order, yielding one pass of a stable sort.

Hollerith Tabulator, Pantograph, Press, and Sorter

© Alon Efrat Introduction to Algorithms L5.42

Origin of radix sort

Hollerith's original 1889 patent alludes to a most-significant-digit-first radix sort:

"The most complicated combinations can readily be counted with comparatively few counters or relays by first assorting the cards according to the first items entering into the combinations, then reassorting each group according to the second item entering into the combination, and so on, and finally counting on a few counters the last item of the combination for each group of cards."

Least-significant-digit-first radix sort seems to be a folk invention originated by machine operators.

© Alon Efrat Introduction to Algorithms L5.43

"Modern" IBM card

- One character per column.

Produced by the WWW Virtual Punch-Card Server.

So, that's why text windows have 80 columns!

© Alon Efrat Introduction to Algorithms L5.44

Web resources on punched-card technology

- [Doug Jones's punched card index](#)
- [Biography of Herman Hollerith](#)
- [The 1890 U.S. Census](#)
- [Early history of IBM](#)
- [Pictures of Hollerith's inventions](#)
- [Hollerith's patent application](#) (borrowed from [Gordon Bell's CyberMuseum](#))
- [Impact of punched cards on U.S. history](#)

© Alon Efrat

Introduction to Algorithms

L5.45