

CSc 372 — Comparative Programming Languages

12 : Haskell — Composing Functions

Christian Collberg
Department of Computer Science
University of Arizona
collberg+372@gmail.com

Copyright © 2005 Christian Collberg

September 16, 2005

1 Composing Functions

We want to discover frequently occurring patterns of computation. These patterns are then made into (often higher-order) functions which can be **specialized** and **combined**. `map f L` and `filter f L` can be specialized and combined:

```
double :: [Int] -> [Int]
double xs = map ((* 2) xs
```

```
positive :: [Int] -> [Int]
positive xs = filter ((<) 0) xs
```

```
doublePos xs = map ((* 2) (filter ((<) 0) xs)
? doublePos [2,3,0,-1,5]
[4, 6, 10]
```

2 Composing Functions...

- Functional composition is a kind of “glue” that is used to “stick” simple functions together to make more powerful ones.
- In mathematics the ring symbol (\circ) is used to compose functions:


$$(f \circ g)(x) = f(g(x))$$

- In Haskell we use the dot (“.”) symbol:

```
infixr 9 .
(.) :: (b->c) -> (a->b) -> (a->c)
(f . g)(x) = f(g(x))
```

3 Composing Functions...

```
(.) :: (b->c) -> (a->b) -> (a->c)
(f . g)(x) = f(g(x))
```



- "." takes two functions f and g as arguments, and returns a new function h as result.
- g is a function of type $a \rightarrow b$.
- f is a function of type $b \rightarrow c$.
- h is a function of type $a \rightarrow c$.
- $(f.g)(x)$ is the same as $z=g(x)$ followed by $f(z)$.

4 Composing Functions...

- We use functional composition to write functions more concisely. These definitions are equivalent:

```
doit x = f1 (f2 (f3 (f4 x)))
doit x = (f1 . f2 . f3 . f4) x
doit = f1 . f2 . f3 . f4
```

- The last form of `doit` is preferred. `doit`'s arguments are **implicit**; it has the same parameters as the composition.
- `doit` can be used in higher-order functions (the second form is preferred):

```
? map (doit) xs
? map (f1 . f2 . f3 . f4) xs
```

5 Example: Splitting Lines

- Assume that we have a function `fill` that splits a string into filled lines:

```
fill :: string -> [string]
fill s = splitLines (splitWords s)
```

- `fill` first splits the string into words (using `splitWords`) and then into lines:

```
splitWords :: string -> [word]
splitLines :: [word] -> [line]
```

- We can rewrite `fill` using function composition:

```
fill = splitLines . splitWords
```

6 Precedence & Associativity

1. "." is **right associative**. I.e.

`f.g.h.i.j = f.(g.(h.(i.j)))`

2. "." has **higher precedence** (binding power) than any other operator, except function application:

`5 + f.g 6 = 5 + (f. (g 6))`

3. "." is associative:

`f . (g . h) = (f . g) . h`

4. "id" is "."'s **identity element**, i.e `id . f = f = f . id`:

`id :: a -> a`
`id x = x`

7 The count Function

- Define a function `count` which counts the number of lists of length n in a list L :

`count 2 [[1], [], [2,3], [4,5], []] => 2`

Using recursion:

```
count :: Int -> [[a]] -> Int
count _ [] = 0
count n (x:xs)
  | length x == n = 1 + count n xs
  | otherwise     = count n xs
```

Using functional composition:

```
count' n = length . filter (==n) . map length
```

8 The count Function...

```
count' n = length . filter (==n) . map length
```

- What does `count'` do?

```
[[1], [], [2,3], [4,5], []]
  ↓ map length
[1,0,2,2,0]
  ↓ filter (==2)
[2,2]
  ↓ length
2
```

- Note that

`count' n xs = length (filter (==n) (map length xs))`

9 The `init` & `last` Functions

- `last` returns the last element of a list.
- `init` returns everything but the last element of a list.

Definitions:

```
last = head . reverse
```

```
init = reverse . tail . reverse
```

Simulations:

```
[1,2,3]  $\xRightarrow{\text{reverse}}$  [3,2,1]  $\xRightarrow{\text{head}}$  3
```

```
[1,2,3]  $\xRightarrow{\text{reverse}}$  [3,2,1]  $\xRightarrow{\text{tail}}$  [2,1]  $\xRightarrow{\text{reverse}}$  [1,2]
```

10 The `any` Function

- `any p xs` returns `True` if `p x == True` for some `x` in `xs`:

```
any ((==)0) [1,2,3,0,5]  $\Rightarrow$  True
```

```
any ((==)0) [1,2,3,4]  $\Rightarrow$  False
```

Using recursion:

```
any :: (a -> Bool) -> [a] -> Bool
any _ [] = False
any p (x:xs) = | p x = True
               | otherwise = any p xs
```

Using composition:

```
any p = or . map p
[1,0,3]  $\xRightarrow{\text{map } ((==)0)}$  [False,True,False]  $\xRightarrow{\text{or}}$  True
```

11 `commaint` Revisited...

- Let's have another look at one simple (!) function, `commaint`.
- `commaint` works on strings, which are simply lists of characters.
- You are ~~not~~ now supposed to understand this!

From the `commaint` documentation:

`[commaint]` takes a single string argument containing a sequence of digits, and outputs the same sequence with commas inserted after every group of three digits, ...

12 commaint Revisited...


Sample interaction:

```
? commaint "1234567"  
1,234,567
```

commaint in Haskell:

```
commaint = reverse . foldr1 (\x y->x++", "++y) .  
  group 3 . reverse  
  where group n = takeWhile (not.null) .  
    map (take n).iterate (drop n)
```

13 commaint Revisited...



14 commaint Revisited...

```
commaint = reverse . foldr1 (\x y->x++", "++y) .  
  group 3 . reverse  
  where group n = takeWhile (not.null) .  
    map (take n).iterate (drop n)
```

- `iterate (drop 3) s` returns the infinite list of strings

```
[s, drop 3 s, drop 3 (drop 3 s),  
 drop 3 (drop 3 (drop 3 s)), ...]
```

- `map (take n) xss` shortens the lists in `xss` to `n` elements.

15 commaint Revisited...

```
commaint = reverse . foldr1 (\x y->x++", "++y) .  
  group 3 . reverse  
  where group n = takeWhile (not.null) .  
    map (take n).iterate (drop n)
```

- `takeWhile (not.null)` removes all empty strings from a list of strings.

- `foldr1 (\x y->x++", "++y) s` takes a list of strings `s` as input. It appends the strings together, inserting a comma in between each pair of strings.

16 Lambda Expressions

- `(\x y->x++", "++y)` is called a **lambda expression**.
- Lambda expressions are simply a way of writing (short) functions inline. Syntax:

```
\ arguments -> expression
```

- Thus, `commaint` could just as well have been written as

```
commaint = ... . foldr1 insert . ...
  where group n = ...
        insert x y = x++", "++y
```

Examples:

```
squareAll xs = map (\ x -> x * x) xs
length = foldl' (\n _ -> n+1) 0
```

17 Summary

- The built-in operator `."` (pronounced “compose”) takes two functions `f` and `g` as argument, and returns a new function `h` as result.
- The new function `h = f . g` combines the behavior of `f` and `g`: applying `h` to an argument `a` is the same as first applying `g` to `a`, and then applying `f` to this result.
- Operators can, of course, also be composed: `((+2) . (*3)) 3` will return `2 + (3 * 3) = 11`.

18 Homework

- Write a function `mid xs` which returns the list `xs` without its first and last element.
 1. use recursion
 2. use `init`, `tail`, and functional composition.
 3. use `reverse`, `tail`, and functional composition.

```
? mid [1,2,3,4,5] => [2,3,4]
? mid [] => ERROR
? mid [1] => ERROR
? mid [1,3] => []
```