# CSc 372

# Comparative Programming Languages

## *9 : Haskell — Curried Functions*

Christian Collberg

collberg+372@gmail.com

Department of Computer Science

University of Arizona

Copyright © 2005 Christian Collberg

# Declaring Infix Functions

- Sometimes it is more natural to use an infix notation for a function application, rather than the normal prefix one:
  - `5 + 6` (infix)
  - `(+) 5 6` (prefix)
- Haskell predeclares some infix operators in the standard prelude, such as those for arithmetic.
- For each operator we need to specify its precedence and associativity. The higher precedence of an operator, the stronger it binds (attracts) its arguments: hence:

```
3 + 5*4   ≡ 3 + (5*4)
3 + 5*4   ≢ (3 + 5) * 4
```



[2]

# Declaring Infix Functions...

- The associativity of an operator describes how it binds when combined with operators of equal precedence. So, is

```
5-3+9      ≡ (5-3)+9 = 11
           OR
5-3+9      ≡ 5-(3+9) = -7
```

  The answer is that + and − associate to the left, i.e. parentheses are inserted from the left.

- Some operators are right associative: `5^3^2` ≡ `5^(3^2)`

- Some operators have free (or no) associativity. Combining operators with free associativity is an error:

```
5 == 4 < 3          ⇒ ERROR
```

# Declaring Infix Functions...

- The syntax for declaring operators:

```
infixr prec oper   -- right assoc.
infixl prec oper   -- left assoc.
infix prec oper    -- free assoc.
```

From the standard prelude:

```
infixl 7 *
infix 7  /, `div`, `rem`, `mod`
infix 4  ==, /=, <, <=, >=, >
```

- An infix function can be used in a prefix function application, by including it in parenthesis. Example:

```
?  (+) 5 ((*) 6 4)
      29
```

# Multi-Argument Functions

# Multi-Argument Functions

- Haskell only supports one-argument functions.
- An $n$-argument function $f(a_1, \cdots, a_n)$ is constructed in either of two ways:
  1. By making the one input argument to $f$ a tuple holding the $n$ arguments.
  2. By letting $f$ "consume" one argument at a time. This is called currying.

| Tuple | Currying |
|---|---|
| `add :: (Int,Int)->Int` | `add :: Int->Int->Int` |
| `add (a, b) = a + b` | `add a b = a + b` |

# Currying

- Currying is the preferred way of constructing multi-argument functions.
- The main advantage of currying is that it allows us to define specialized versions of an existing function.
- A function is specialized by supplying values for one or more (but not all) of its arguments.
- Let's look at Haskell's plus operator `(+)`. It has the type

```
(+) :: Int -> (Int -> Int).
```

- If we give two arguments to `(+)` it will return an `Int`:

```
(+) 5 3 ⇒ 8
```

# Currying...

- If we just give one argument (5) to `(+)` it will instead return a function which "adds 5 to things". The type of this specialized version of `(+)` is `Int -> Int`.
- Internally, Haskell constructs an intermediate – specialized – function:

```
add5 ::  Int -> Int
add5 a = 5 + a
```

- Hence, `(+) 5 3` is evaluated in two steps. First `(+) 5` is evaluated. It returns a function which adds 5 to its argument. We apply the second argument 3 to this new function, and the result 8 is returned.

# Currying...

- To summarize, Haskell only supports one-argument functions. Multi-argument functions are constructed by successive application of arguments, one at a time.
- Currying is named after logician Haskell B. Curry (1900-1982) who popularized it. It was invented by Schönfinkel in 1924. Schönfinkeling doesn't sound too good...
- Note: Function application (`f x`) has higher precedence (10) than any other operator. Example:

```
f 5 + 1      ⇔ (f 5) + 1
f 5 6        ⇔ (f 5) 6
```

# Currying Example

- Let's see what happens when we evaluate `f 3 4 5`, where `f` is a 3-argument function that returns the sum of its arguments.

```
f ::  Int -> (Int -> (Int -> Int))
f x y z = x + y + z

f 3 4 5 ≡ ((f 3) 4) 5
```

# Currying Example...

- `(f 3)` returns a function `f' y z` (`f'` is a specialization of `f`) that adds 3 to its next two arguments.

```
f 3 4 5 ≡ ((f 3) 4) 5 ⇒ (f' 4) 5
```

```
f' ::  Int -> (Int -> Int)
f' y z = 3 + y + z
```

# Currying Example...

- `(f' 4)` (≡ `(f 3) 4`) returns a function `f''z` (`f''` is a specialization of `f'`) that adds (3+4) to its argument.

```
f 3 4 5 ≡ ((f 3) 4) 5 ⇒ (f' 4) 5
          ⇒ f'' 5
```

```
f'' :: Int -> Int
f'' z = 3 + 4 + z
```

- Finally, we can apply `f''` to the last argument (5) and get the result:

```
f 3 4 5 ≡ ((f 3) 4) 5 ⇒ (f' 4) 5
          ⇒ f'' 5 ⇒ 3+4+5 ⇒ 12
```

# Currying Example

## The Combinatorial Function:

- The combinatorial function $\binom{n}{r}$ "n choose r", computes the number of ways to pick $r$ objects from $n$.

$$\binom{n}{r} = \frac{n!}{r! * (n-r)!}$$

## In Haskell:

```
comb ::  Int -> Int -> Int
comb n r = fact n/(fact r*fact(n-r))

?  comb 5 3
   10
```

# Currying Example...

```
comb :: Int -> Int -> Int
comb n r = fact n/(fact r*fact(n-r))
comb 5 3 ⇒ (comb 5) 3 ⇒
           comb^5 3 ⇒
           120 / (fact 3 * (fact 5-3)) ⇒
           120 / (6 * (fact 5-3)) ⇒
           120 / (6 * fact 2) ⇒
           120 / (6 * 2) ⇒
           120 / 12 ⇒
           10
comb^5 r = 120 / (fact r * fact(5-r))
```

- `comb`$^5$ is the result of partially applying `comb` to its first argument.

# Associativity

- Function application is left-associative:

```
f a b = (f a) b | f a b ≠ f (a b)
```

- The function space symbol `'->'` is right-associative:

```
a -> b -> c = a -> (b -> c)
a -> b -> c ≠ (a -> b) -> c
```

- `f` takes an `Int` as argument and returns a function of type `Int -> Int`. `g` takes a function of type `Int -> Int` as argument and returns an `Int`:

```
f' ::  Int -> (Int -> Int)
       ⇕
f ::   Int -> Int -> Int
       ⇵
g ::   (Int -> Int) -> Int
```

# What's the Type, Mr. Wolf?

- If the type of a function `f` is

  $$\texttt{t}_1 \texttt{ -> } \texttt{t}_2 \texttt{ -> } \cdots \texttt{ -> } \texttt{t}_n \texttt{ -> t}$$

- and `f` is applied to arguments

  $$\texttt{e}_1\texttt{::t}_1\texttt{, } \texttt{e}_2\texttt{::t}_2\texttt{, } \cdots\texttt{, } \texttt{e}_k\texttt{::t}_k\texttt{,}$$

- and $\texttt{k} \leq \texttt{n}$
- then the result type is given by cancelling the types $\texttt{t}_1 \cdots \texttt{t}_k$:

  $$\not{\texttt{t}}_1 \texttt{ -> } \not{\texttt{t}}_2 \texttt{ -> } \cdots \texttt{ -> } \not{\texttt{t}}_k \texttt{ -> } \texttt{t}_{k+1} \texttt{ -> } \cdots \texttt{ -> } \texttt{t}_n \texttt{ -> t}$$

- Hence, $\texttt{f e}_1\ \texttt{e}_2\ \cdots\ \texttt{e}_k$ returns an object of type

  $$\texttt{t}_{k+1} \texttt{ -> } \cdots \texttt{ -> } \texttt{t}_n \texttt{ -> t}.$$

- This is called the Rule of Cancellation.

# Homework

- Define an operator `$$` so that `x $$ xs` returns `True` if `x` is an element in `xs`, and `False` otherwise.

Example:

```
?  4 $$ [1,2,5,6,4,7]
   True

?  4 $$ [1,2,3,5]
   False

?  4 $$ []
   False
```