CSc 372

Comparative Programming Languages

10 : Haskell — Curried Functions

Department of Computer Science
University of Arizona

collberg@gmail.com

Copyright © 2011 Christian Collberg

Christian Collberg

Infix Functions

Declaring Infix Functions

- Sometimes it is more natural to use an infix notation for a function application, rather than the normal prefix one:
  - `5 + 6` (infix)
  - `(+) 5 6` (prefix)
- Haskell predeclares some infix operators in the standard prelude, such as those for arithmetic.
- For each operator we need to specify its precedence and associativity. The higher precedence of an operator, the stronger it binds (attracts) its arguments: hence:

  `3 + 5*4` $\equiv$ `3 + (5*4)`
  `3 + 5*4` $\not\equiv$ `(3 + 5) * 4`

Declaring Infix Functions...

- The associativity of an operator describes how it binds when combined with operators of equal precedence. So, is

  `5-3+9` $\equiv$ `(5-3)+9 = 11`
  OR
  `5-3+9` $\equiv$ `5-(3+9) = -7`

  The answer is that + and - associate to the left, i.e. parentheses are inserted from the left.
- Some operators are right associative: `5^3^2` $\equiv$ `5^(3^2)`
- Some operators have free (or no) associativity. Combining operators with free associativity is an error:

  `5 == 4 < 3` $\Rightarrow$ ERROR

Declaring Infix Functions...

- The syntax for declaring operators:

```
infixr prec oper  -- right assoc.
infixl prec oper  -- left assoc.
infix prec oper   -- free assoc.
```

From the standard prelude:

```
infixl 7 *
infix 7  /, `div`, `rem`, `mod`
infix 4  ==, /=, <, <=, >=, >
```

- An infix function can be used in a prefix function application, by including it in parenthesis. Example:

```
?  (+) 5 ((*) 6 4)
     29
```

Multi-Argument Functions

Multi-Argument Functions

- Haskell only supports one-argument functions.
- An n-argument function $f(a_1, \cdots, a_n)$ is constructed in either of two ways:
  1. By making the one input argument to f a tuple holding the n arguments.
  2. By letting f "consume" one argument at a time. This is called currying.

Tuple	Currying
`add :: (Int,Int)->Int`	`add :: Int->Int->Int`
`add (a, b) = a + b`	`add a b = a + b`

Currying

- Currying is the preferred way of constructing multi-argument functions.
- The main advantage of currying is that it allows us to define specialized versions of an existing function.
- A function is specialized by supplying values for one or more (but not all) of its arguments.
- Let's look at Haskell's plus operator `(+)`. It has the type

  `(+) :: Int -> (Int -> Int)`.
- If we give two arguments to `(+)` it will return an `Int`:

  `(+) 5 3` $\Rightarrow$ `8`

Currying...

- If we just give one argument (5) to (+) it will instead return a function which "adds 5 to things". The type of this specialized version of (+) is `Int -> Int`.
- Internally, Haskell constructs an intermediate – specialized – function:

```
add5 ::  Int -> Int
add5 a = 5 + a
```

- Hence, `(+) 5 3` is evaluated in two steps. First `(+) 5` is evaluated. It returns a function which adds 5 to its argument. We apply the second argument 3 to this new function, and the result 8 is returned.

Currying...

- To summarize, Haskell only supports one-argument functions. Multi-argument functions are constructed by successive application of arguments, one at a time.
- Currying is named after logician Haskell B. Curry (1900-1982) who popularized it. It was invented by Schönfinkel in 1924. Schönfinkeling doesn't sound too good...
- Note: Function application (`f x`) has higher precedence (10) than any other operator. Example:

```
f 5 + 1      ⇔ (f 5) + 1
f 5 6        ⇔ (f 5) 6
```

Currying Example

- Let's see what happens when we evaluate `f 3 4 5`, where `f` is a 3-argument function that returns the sum of its arguments.

```
f ::  Int -> (Int -> (Int -> Int))
f x y z = x + y + z

f 3 4 5 ≡ ((f 3) 4) 5
```

Currying Example...

- `(f 3)` returns a function `f' y z` (`f'` is a specialization of `f`) that adds 3 to its next two arguments.

```
f 3 4 5 ≡ ((f 3) 4) 5 ⇒ (f' 4) 5

f' ::  Int -> (Int -> Int)
f' y z = 3 + y + z
```

Currying Example. . .

- `(f' 4)` (≡ `(f 3) 4`) returns a function `f''z` (`f''` is a specialization of `f'`) that adds (3+4) to its argument.

```
f 3 4 5 ≡ ((f 3) 4) 5 ⇒ (f' 4) 5
        ⇒ f'' 5

f'' ::  Int -> Int
f'' z = 3 + 4 + z
```

- Finally, we can apply `f''` to the last argument (5) and get the result:

```
f 3 4 5 ≡ ((f 3) 4) 5 ⇒ (f' 4) 5
        ⇒ f'' 5 ⇒ 3+4+5 ⇒ 12
```

Currying Example

The Combinatorial Function:

- The combinatorial function $\binom{n}{r}$ "n choose r", computes the number of ways to pick r objects from n.

$$\binom{n}{r} = \frac{n!}{r! * (n-r)!}$$

In Haskell:

```
comb ::  Int -> Int -> Int
comb n r = fact n/(fact r*fact(n-r))

?  comb 5 3
   10
```

Currying Example. . .

```
comb ::  Int -> Int -> Int
comb n r = fact n/(fact r*fact(n-r))
```

```
comb 5 3 ⇒ (comb 5) 3 ⇒
           comb5 3 ⇒
           120 / (fact 3 * (fact 5-3)) ⇒
           120 / (6 * (fact 5-3)) ⇒
           120 / (6 * fact 2) ⇒
           120 / (6 * 2) ⇒
           120 / 12 ⇒
           10
```

```
comb5 r = 120 / (fact r * fact(5-r))
```

- $comb^5$ is the result of partially applying comb to its first argument.

Associativity

- Function application is left-associative:
  `f a b = (f a) b` | `f a b` ≠ `f (a b)`
- The function space symbol '`->`' is right-associative:
  `a -> b -> c = a -> (b -> c)`
  `a -> b -> c` ≠ `(a -> b) -> c`
- `f` takes an `Int` as argument and returns a function of type `Int -> Int`. `g` takes a function of type `Int -> Int` as argument and returns an `Int`:

```
f' ::  Int -> (Int -> Int)
       ⇕
f ::   Int -> Int -> Int
       ⇕
g ::   (Int -> Int) -> Int
```

What's the Type, Mr. Wolf?

- If the type of a function `f` is

  t_1 -> t_2 -> $\cdots$ -> t_n -> t

- and `f` is applied to arguments

  e_1::t_1, e_2::t_2, $\cdots$, e_k::t_k,

- and $k \leq n$
- then the result type is given by cancelling the types $t_1 \cdots t_k$:

  $\not{t}_1$ -> $\not{t}_2$ -> $\cdots$ -> $\not{t}_k$ -> t_{k+1} -> $\cdots$ -> t_n -> t

- Hence, f e_1 e_2 $\cdots$ e_k returns an object of type

  t_{k+1} -> $\cdots$ -> t_n -> t.

- This is called the Rule of Cancellation.

flip

```
flip       :: (a -> b -> c) -> b -> a -> c
flip f x y  = f y x
```

- The `flip` function takes a function `f x y` (`f` is the function and `x` and `y` its two arguments, and reorders the arguments!
- Or, more correctly, `flip` returns a new function `f y x`.
- You can use this when you want to specialize a function by supplying an argument, but the function takes its arguments in the "wrong order."

flip...

- Consider the `(!!)` function, for example:

```
> :type (!!)
(!!) :: [a] -> Int -> a
> :type flip(!!)
flip (!!) :: Int -> [a] -> a
> (!!) [1..10] 2
3
> (flip (!!)) 2 [1..10]
3
```

- Now you can write a function `fifth` using `(!!)` which returns the fifth element of a list:

```
fifth :: [a] -> a
fifth = (flip (!!)) 5
```

Homework

- Define an operator `$$` so that `x $$ xs` returns `True` if `x` is an element in `xs`, and `False` otherwise.

Example:

```
? 4 $$ [1,2,5,6,4,7]
  True

? 4 $$ [1,2,3,5]
  False

? 4 $$ []
  False
```

Homework

- Define an function `drop3` which takes a list as argument and returns a new list with the first three elements removed.
- Use currying!

Homework

```
> :type elem
elem :: Eq a => a -> [a] -> Bool
> elem 3 [1..10]
```

- The `elem` function returns true if the first argument is a member of the second (a list).
- Write a function `has3 xs` which returns true if `xs` (a list) contains the number 3.
- Write a function `isSmallPrime x` which returns true if `x` is one of the numbers 2,3,5,7.
- Use currying!

```
> isSmallPrime 2
True
> has3 [1]
False
```