

CSc 372

Comparative Programming Languages

21 : Prolog — Execution

Department of Computer Science
University of Arizona

collberg@gmail.com

Copyright © 2011 Christian Collberg

Christian Collberg

Executing Prolog

- Now that we know about matching, we can take a closer look at how Prolog tries to satisfy goals.
- In general, to solve a goal

$$G = G_1, G_2, \dots, G_m,$$

Prolog will first try to solve the sub-goal G_1 .

- It solves a sub-goal G_1 it will look for a rule

$$H_i :- B_1, \dots, B_n$$

in the database, such that G_1 and H_i will match.

- Any variable substitutions resulting from the match will be stored in a variable θ .

Execution

Executing Prolog . . .

- A new goal will be constructed by replacing G_1 with B_1, \dots, B_n , yielding

$$G' = B_1, \dots, B_n, G_2, \dots, G_m.$$

If $n = 0$ the new goal will be shorter and we'll be one step closer to a solution to G !


- Any new variable bindings from θ are applied to the new goal, yielding G'' .
- We recursively try to find a solution to G'' .

Executing Prolog...

```

FUNC Execute ( $G = G_1, G_2, \dots, G_m$ ; Result);
  IF IsEmpty( $G$ ) THEN Result := Yes
  ELSE
    Result := No;
     $i := 1$ ;
    WHILE Result=No &  $i \leq \text{NoOfClauses}$  DO
      Clause :=  $H_i :- B_1, \dots, B_n$ ;
      IF Unify( $G_1$ , Clause,  $\theta$ ) THEN
         $G' := B_1, \dots, B_n, G_2, \dots, G_m$ ;
         $G'' := \text{substitute}(G', \theta)$ ;
        Execute( $G''$ , Result);
      ENDIF;
       $i := i + 1$ ;
    ENDDO
  ENDIF

```



Example


Northern Exposure Example

```

% From the Northern Exposure FAQ
% friend(of, kind(name, regular)).
friend(maggie, person(eve, yes)).
friend(maggie, moose(morty, yes)).
friend(maggie, person(harry, no)).
friend(maggie, person(bruce, no)).
friend(maggie, person(glenn, no)).
friend(maggie, person(dave, no)).
friend(maggie, person(rick, no)).
friend(maggie, person(mike, yes)).
friend(maggie, person(joel, yes)).

```

Maggie (Janine Turner)




Northern Exposure Example...





```
cause_of_death(morty, copper_deficiency).  
cause_of_death(harry, potato_salad).  
cause_of_death(bruce, fishing_accident).  
cause_of_death(glenn, missile).  
cause_of_death(dave, hypothermia).  
cause_of_death(rick, hit_by_satellite).  
cause_of_death(mike, none_yet).  
cause_of_death(joel, none_yet).
```



```
male(morty). male(harry). male(bruce).  
male(glenn). male(dave). male(rick).  
male(mike). male(joel). female(eve).
```

Northern Exposure Example...

```
alive(X) :- cause_of_death(X, none_yet).  
  
pastime(eve, hypochondria).  
pastime(mike, hypochondria).  
pastime(X, golf) :- job(X, doctor).  
  
job(mike, lawyer). job(adam, chef).  
job(maggie, pilot). job(joel, doctor).  
  
?- friend(maggie, person(B, yes)),  
     male(B),  
     alive(B),  
     pastime(B, golf).
```











Northern Exposure Example...

- We skip a step here.
- pastime(mike, golf) unifies with
 $\text{pastime}(X, \text{golf}) :- \text{job}(X, \text{doctor}).$
- .
- However, $\text{job}(mike, \text{doctor})$ fails, and we backtrack all the way up to the original query.





Readings and References

- Read [Clocksin-Mellish, Section 4.1](#).
- See <http://www.moosefest.org> for information about the annual Moosefest.
- See <http://members.lycos.co.uk/janineturner/engl/index.html> for pictures of Janine Turner, who plays Maggie.
- See <http://home.comcast.net/~mcnotes/mcnotes.html> for show transcripts.

Summary

- A term is either a
 - a constant (an atom or integer)
 - a variable
 - a structure
- Two terms *match* if
 - there exists a variable substitution θ which makes the terms identical.
- Once a variable becomes instantiated, it stays instantiated.
- Backtracking *undoes* variable instantiations.
- Prolog searches the database sequentially (from top to bottom) until a matching clause is found.