

CSc 372 — Comparative Programming Languages

7 : Haskell — Patterns

Christian Collberg
Department of Computer Science
University of Arizona
collberg@gmail.com

Copyright © 2011 Christian Collberg

August 23, 2011

1 Pattern Matching

- Haskell has a notation (called **patterns**) for defining functions that is more convenient than conditional (**if-then-else**) expressions.
- Patterns are particularly useful when the function has more than two cases.

Pattern Syntax: _____

```
function_name pattern_1 = expression_1
function_name pattern_2 = expression_2
...
function_name pattern_n = expression_n
```

2 Pattern Matching...

```
fact n = if n == 0 then
  1
else
  n * fact (n-1)
```

fact Revisited: _____

```
fact :: Int -> Int
fact 0 = 1
fact n = n * fact (n-1)
```

3 Pattern Matching...

- Pattern matching allows us to have alternative definitions for a function, depending on the format of the actual parameter. Example:

```
isNice "Jenny" = "Definitely"
isNice "Johanna" = "Maybe"
isNice "Chris" = "No Way"
```

4 Pattern Matching...

- We can use pattern matching as a design aid to help us make sure that we're considering all possible inputs.
- Pattern matching simplifies taking structured function arguments apart. Example:

```
fun (x:xs) = x ⊕ fun xs
      ⇔
fun xs = head xs ⊕ fun (tail xs)
```

5 Pattern Matching...

- When a function f is applied to an argument, Haskell looks at each definition of f until the argument matches one of the patterns.

```
not True = False
not False = True
```

6 Pattern Matching...

- In most cases a function definition will consist of a number of mutually exclusive patterns, followed by a **default** (or **catch-all**) pattern:

```
diary "Monday" = "Woke up"
diary "Sunday" = "Slept in"
diary anyday = "Did something else"
```

```
diary "Sunday" ⇒ "Slept in"
diary "Tuesday" ⇒ "Did something else"
```

7 Pattern Matching – Integer Patterns

- There are several kinds of integer patterns that can be used in a function definition.

Pattern	Syntax	Example	Description
variable	var_name	fact n = ...	n matches any argument
constant	literal	fact 0 = ...	matches the value
wildcard	_	five _ = 5	_ matches any argument
(n+k) pat.	(n+k)	fact (n+1) = ...	(n+k) matches any integer $\geq k$

8 Pattern Matching – List Patterns

- There are also special patterns for matching and (taking apart) lists.

Pattern	Syntax	Example	Description
cons	(x:xs)	len (x:xs) = ...	matches non-empty list
empty	[]	len [] = 0	matches the empty list
one-elem	[x]	len [x] = 1	matches a list with exactly 1 element.
two-elem	[x,y]	len [x,y] = 2	matches a list with exactly 2 elements.

9 The sumlist Function

_____ Using conditional expr: _____

```
sumlist :: [Int] -> Int
sumlist xs = if xs == [] then 0
             else head xs + sumlist(tail xs)
```

_____ Using patterns: _____

```
sumlist :: [Int] -> Int
sumlist [] = 0
sumlist (x:xs) = x + sumlist xs
```

- Note that patterns are checked top-down! The ordering of patterns is therefore important.

10 The length Function Revisited

_____ Using conditional expr: _____

```
len :: [Int] -> Int
len s = if s == [] then 0 else 1 + len (tail s)
```

_____ Using patterns: _____

```
len :: [Int] -> Int
len [] = 0
len (_:xs) = 1 + len xs
```

- Note how similar len and sumlist are. Many recursive functions on lists will have this structure.

11 The fact Function Revisited

_____ Using conditional expr: _____

```
fact n = if n == 0 then 1 else n * fact (n-1)
```

_____ Using patterns: _____

```
fact' :: Int -> Int
fact' 0 = 1
fact' (n+1) = (n+1) * fact' n
```

- Are fact and fact' identical?

```
fact (-1)    => Stack overflow
fact' (-1)   => Program Error
```

- The second pattern in fact' only matches positive integers (≥ 1).

12 Summary

- Functional languages use recursion rather than iteration to express repetition.
- We have seen two ways of defining a recursive function: using conditional expressions (`if-then-else`) or pattern matching.
- A pattern can be used to take lists apart without having to explicitly invoke `head` and `tail`.
- Patterns are checked from top to bottom. They should therefore be ordered from specific (at the top) to general (at the bottom).

13 Homework

- Define a recursive function `addints` that returns the sum of the integers from 1 up to a given upper limit.
- Simulate the execution of `addints 4`.

```
addints :: Int -> Int
addints a = ...
```

```
? addints 5
15
```

```
? addints 2
3
```

14 Homework

- Define a recursive function `member` that takes two arguments – an integer `x` and a list of integers `L` – and returns `True` if `x` is an element in `L`.
- Simulate the execution of `member 3 [1,4,3,2]`.

```
member :: Int -> [Int] -> Bool
member x xs = ...
```

```
? member 1 [1,2,3]
True
```

```
? member 4 [1,2,3]
False
```

15 Homework

- Write a recursive function `memberNum x xs` which returns the number of times `x` occurs in `xs`.
- Use `memberNum` to write a function `unique xs` which returns a list of elements from `xs` that occurs exactly once.

```
memberNum :: Int -> [Int] -> Int
unique    :: [Int] -> [Int]
```

```
? memberNum 5 [1,5,2,3,5,5]
```

```
3
```

```
? unique [2,4,2,1,4]
```

```
[1]
```

16 Homework

- Ackerman's function is defined for nonnegative integers:

$$\begin{aligned}A(0, n) &= n + 1 \\A(m, 0) &= A(m - 1, 1) \\A(m, n) &= A(m - 1, A(m, n - 1))\end{aligned}$$

- Use pattern matching to implement Ackerman's function.
- Flag all illegal inputs using the built-in function `error S` which terminates the program and prints the string `S`.

```
ackerman :: Int -> Int -> Int
ackerman 0 5 ⇒ 6
ackerman (-1) 5 ⇒ ERROR
```