

CSc 372

# Comparative Programming Languages

## 7 : Haskell — Patterns

Department of Computer Science  
University of Arizona

[collberg@gmail.com](mailto:collberg@gmail.com)

Copyright © 2013 Christian Collberg

# Pattern Matching

- Haskell has a notation (called **patterns**) for defining functions that is more convenient than conditional (`if-then-else`) expressions.
- Patterns are particularly useful when the function has more than two cases.

\_\_\_\_\_ Pattern Syntax: \_\_\_\_\_

```
function_name pattern_1 = expression_1
function_name pattern_2 = expression_2
...
function_name pattern_n = expression_n
```

# Pattern Matching...

```
fact n = if n == 0 then
  1
  else
    n * fact (n-1)
```

\_\_\_\_\_ fact Revisited: \_\_\_\_\_

```
fact :: Int -> Int
fact 0 = 1
fact n = n * fact (n-1)
```

## Pattern Matching...

- Pattern matching allows us to have alternative definitions for a function, depending on the format of the actual parameter.

Example:

```
isNice "Jenny" = "Definitely"
```

```
isNice "Johanna" = "Maybe"
```

```
isNice "Chris" = "No Way"
```

## Pattern Matching...

- We can use pattern matching as a design aid to help us make sure that we're considering all possible inputs.
- Pattern matching simplifies taking structured function arguments apart. Example:

```
fun (x:xs) = x ⊕ fun xs
    ⇔
fun xs = head xs ⊕ fun (tail xs)
```

# Pattern Matching...

- When a function  $f$  is applied to an argument, Haskell looks at each definition of  $f$  until the argument matches one of the patterns.

```
not True = False
```

```
not False = True
```

## Pattern Matching...

- In most cases a function definition will consist of a number of mutually exclusive patterns, followed by a **default** (or **catch-all**) pattern:

```
diary "Monday" = "Woke up"  
diary "Sunday" = "Slept in"  
diary anyday = "Did something else"
```

```
diary "Sunday" ⇒ "Slept in"  
diary "Tuesday" ⇒ "Did something else"
```

# Pattern Matching – Integer Patterns

- There are several kinds of integer patterns that can be used in a function definition.
- Use the flag `-XNPlusKPatterns` to turn on  $n+k$  patterns in `ghc`.

Pattern	Syntax	Example	Description
variable	<code>var_name</code>	<code>fact n = ...</code>	<code>n</code> matches any argument
constant	literal	<code>fact 0 = ...</code>	matches the value
wildcard	<code>_</code>	<code>five _ = 5</code>	<code>_</code> matches any argument
$(n+k)$ pat.	$(n+k)$	<code>fact (n+1) = ...</code>	$(n+k)$ matches any integer $\geq k$



## Pattern Matching – List Patterns

- There are also special patterns for matching and (taking apart) lists.

Pattern	Syntax	Example	Description
cons	$(x:xs)$	$\text{len } (x:xs) = \dots$	matches non-empty list
empty	$[\ ]$	$\text{len } [\ ] = 0$	matches the empty list
one-elem	$[x]$	$\text{len } [x] = 1$	matches a list with exactly 1 element.
two-elem	$[x,y]$	$\text{len } [x,y] = 2$	matches a list with exactly 2 elements.

# The sumlist Function

\_\_\_\_\_ Using conditional expr: \_\_\_\_\_

```
sumlist :: [Int] -> Int
sumlist xs = if xs == [ ] then 0
              else head xs + sumlist(tail xs)
```

\_\_\_\_\_ Using patterns: \_\_\_\_\_

```
sumlist :: [Int] -> Int
sumlist [ ] = 0
sumlist (x:xs) = x + sumlist xs
```

- Note that patterns are checked top-down! The ordering of patterns is therefore important.

# The length Function Revisited

\_\_\_\_\_ Using conditional expr: \_\_\_\_\_

```
len :: [Int] -> Int
len s = if s == [ ] then 0 else 1 + len (tail s)
```

\_\_\_\_\_ Using patterns: \_\_\_\_\_

```
len :: [Int] -> Int
len [ ] = 0
len (_:xs) = 1 + len xs
```

- Note how similar `len` and `sumlist` are. Many recursive functions on lists will have this structure.

# The fact Function Revisited

\_\_\_\_\_ Using conditional expr: \_\_\_\_\_

```
fact n = if n == 0 then 1 else n * fact (n-1)
```

\_\_\_\_\_ Using patterns: \_\_\_\_\_

```
fact' :: Int -> Int
fact' 0 = 1
fact' (n+1) = (n+1) * fact' n
```

- Are fact and fact' identical?

fact (-1) ⇒ Stack overflow

fact' (-1) ⇒ Program Error

- The second pattern in fact' only matches positive integers ( $\geq 1$ ).

# Summary

- Functional languages use recursion rather than iteration to express repetition.
- We have seen two ways of defining a recursive function: using conditional expressions (`if-then-else`) or pattern matching.
- A pattern can be used to take lists apart without having to explicitly invoke `head` and `tail`.
- Patterns are checked from top to bottom. They should therefore be ordered from specific (at the top) to general (at the bottom).

# Exercise

- Define a recursive function `addints` that returns the sum of the integers from 1 up to a given upper limit.
- Simulate the execution of `addints 4`.

```
addints :: Int -> Int
addints a = ...
```

```
? addints 5
15
```

```
? addints 2
3
```

# Exercise

- Define a recursive function `member` that takes two arguments – an integer `x` and a list of integers `L` – and returns `True` if `x` is an element in `L`.
- Simulate the execution of `member 3 [1,4,3,2]`.

```
member :: Int -> [Int] -> Bool
member x xs = ...
```

```
? member 1 [1,2,3]
```

```
True
```

```
? member 4 [1,2,3]
```

```
False
```

# Exercise

- Write a recursive function `memberNum x xs` which returns the number of times `x` occurs in `xs`.
- Use `memberNum` to write a function `unique xs` which returns a list of elements from `xs` that occurs exactly once.

```
memberNum :: Int -> [Int] -> Int
unique    :: [Int] -> [Int]
```

```
? memberNum 5 [1,5,2,3,5,5]
```

```
3
```

```
? unique [2,4,2,1,4]
```

```
[1]
```



## Exercise

- Ackerman's function is defined for nonnegative integers:

$$A(0, n) = n + 1$$

$$A(m, 0) = A(m - 1, 1)$$

$$A(m, n) = A(m - 1, A(m, n - 1))$$

- Use pattern matching to implement Ackerman's function.
- Flag all illegal inputs using the built-in function `error S` which terminates the program and prints the string `S`.

```
ackerman :: Int -> Int -> Int
```

```
ackerman 0 5 ⇒ 6
```

```
ackerman (-1) 5 ⇒ ERROR
```